



Previous Name: Mysella LA

Shell Mysella S3 N 30

Low Ash Stationary Gas Engine Oil

- *Reliable Protection*
- *Low Ash Content for Four Stroke Engines*

Shell Mysella S3 N is a high performance quality oil blended for use in 4-stroke, spark-ignition engines which require a 'low ash' oil and use natural gas as fuel.

Shell Mysella S3 N satisfies the new generation of stationary gas engines designed to meet the emerging legislation limiting emissions of NO_x, and those which employ the latest 'lean' or 'clean' burn technology.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- **Extended oil life**

Significantly prolongs oil life relative to previous generation gas engine oils by resisting oxidation and nitration, viscosity increase and the formation of harmful acids.

- **Engine protection**

Shell Mysella S3 N is formulated with low ash and low phosphorus offering extended life to valves and spark plugs and full compatibility with emission catalysts.

- Fairbank Morse
- Dresser Rand

For engines under warranty, Shell advises contact with the engine manufacturer and Shell representative to choose the appropriate oil given the equipment operating conditions and customer maintenance practices.

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Help Desk.

Main Applications



- Spark-ignited gas engines fueled by natural gas
- May also be used for landfill and biogases

Specifications, Approvals & Recommendations

Shell Mysella S3 N is suitable in engine types where a "low ash" oil is required.

Shell Mysella S3 N Meets requirements of:

- Caterpillar Stationary Gas Engines
- Cameron System

Typical physical Characteristics

Properties			Method	Shell Mysella S3 N 30
SAE Viscosity Grade				30
Kinematic Viscosity	@40°C	mm ² /s	ASTM D445	105
Kinematic Viscosity	@100°C	mm ² /s	ASTM D445	11
density	@15°C	kg/m ³	ASTM D4052	890
Flash Point, closed cup		°C	ASTM D93A	218
Pour Point		°C	ISO 3016	-21
BN	mg	KOH/g	ASTM D2896	5
Sulfated Ash		%wt	ISO 3987	0.45
phosphorus		ppm	ASTM D4047	300

These characteristics are typical of current production. While future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

Shell Mysella S3 N is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com/>

• Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Additional Information

• Oil Analysis

For optimum results regular oil analysis is strongly recommended

• Advice

Product recommendations for applications and specifications not covered here may be obtained from your Shell representative.

Note: this product is not designed for automotive gas engines